

TM310

**Dynamic
gooseneck microphone
with ON/OFF switch**

Article-No.:
6119-000-000-05



Product:

Characteristics

- Dynamic microphone capsule
- Unidirectional noise canceling
- Rugged housing with gooseneck
- Long life slide switch

Application range

- Radio and PA systems in mobile and fixed applications

Scope of delivery

- Gooseneck microphone with cable

Technical Data:

General

Housing:	Brass , matte black plasma coated
Gooseneck:	Steel coil with external brass winding, black
Dimensions:	Length 792 mm, Head Ø 29 mm, Body Ø 24 mm Gooseneck Ø 15 mm
Weight:	726 g (25.6 oz)
Connection cable:	Length 2.7 m, 4-wires, 2 Wires shielded, without connector
Operating and display elements:	ON/OFF switch (slide switch), black
Storage temperature:	-30 °C to +70 °C (-22 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range:	300 Hz to 6 kHz at -10 dB
Sensitivity:	1.5 mV/Pa (-56 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)